

From: Rod Yanez

Date: 25 Oct 2019

Subject: EPL Data 2019 – monitoring period 4 Sep 2018 – 3 Sep 2019

B1 Number of pollution complaints

Pollution Complaint Category	Number of Complaints
Air	8
Noise	1

B2 Concentration Monitoring Summary

Testing for emission compliance was executed over one day. During sampling the facility was operating under normal plant operating conditions.

USEPA Method 18 (TM-34) was used to perform testing for Volatile Organic Compounds. AS/NZS 4323.3:2001 (OM-7) was used for testing of Odour at EPL Point 1, 2 and 3 in accordance with EPL requirements.

One sample for each analyte was taken from EPL Points 1, 2 and 3.

Total Volatile Organic Compounds concentrations at EPL Point 1, 2 and 3 were 2.5 mg/m³, 1.4 mg/m³ and 2.1 mg/m³ respectively.

Odour concentrations for EPL Point 1, 2 and 3 were 560 OU, 850 OU and 310 OU respectively.

Table 4-3: Results for EPL Point 1

Pollutant	Isokinetic rate (%)	Concentration	Emission rate	Concentration Limit	Compliant with Limit
Total VOCs as n-Propane	N/A	2.5 mg/m ³	0.003 g/s	40 mg/m ³	✓
Odour	N/A	560 OU	759 OU.m ³ /s	N/A	N/A

Table 4-6: Results for EPL Point 2

Pollutant	Isokinetic rate (%)	Concentration	Emission rate	Concentration Limit	Compliant with Limit
Total VOCs as n-Propane	N/A	1.4 mg/m ³	0.001 g/s	N/A	N/A
Odour	N/A	850 OU	888 OU.m ³ /s	N/A	N/A

Table 4-9: Results for EPL Point 3

Pollutant	Isokinetic rate (%)	Concentration	Emission rate	Concentration Limit	Compliant with Limit
Total VOCs as n-Propane	N/A	2.1 mg/m ³	0.02 g/s	40 mg/m ³	✓
Odour	N/A	310 OU	2,883 OU.m ³ /s	N/A	N/A